# **SUL 191 w**

Item no.: 1910011



### Time and light control Analogue time switches

### Description

- Analogue time switch
- 1 channel
- Weekly program
- With power reserve (NiMH rechargeable battery)
- 84 switching segments
- Quartz controlled
- Shortest switching time: 2 hours
- Clock hands for time display and in addition 12/24 hour recognition
- Simple summer/winter time correction
- Time can be changed clockwise or anti-clockwise
- DuoFix spring terminals
- For 2 conductors each
- Wire or strand (with or without wire end sleeve)
- Wire diameter: 0.5 2.5 mm<sup>2</sup>
- Button for releasing plug-in connection
- Switching preselection
- Manual switch with 3 positions: Continuous ON/AUTO/continuous OFF
- Switching status display



### Technical data

	SUL 191 w
Operating voltage	110 - 230 V AC
Frequency	50 – 60 Hz
Number of channels	1
Width	3 modules
Installation type	DIN rail
Type of connection	DuoFix spring terminals
Drive	Quartz-controlled stepper motor
Program	Weekly program
Power reserve	3 days approx. 1.5 days at 110 V
Switching capacity at 250 V AC, cos φ = 1	16 A

	SUL 191 w
Switching capacity at 250 V AC, $\cos \phi = 0.6$	4 A
Incandescent/halogen lamp load	1100 W
LED lamp < 2 W	20 W
LED lamp 2-8 W	180 W
LED lamp > 8 W	180 W
Shortest switching times	2 h
Programmable every	2 h
Time accuracy at 25 °C	≤ ± 1 s/day (quartz)
Type of contact	Changeover contact

# **SUL 191 w**

Item no.: 1910011




#### Technical data

	SUL 191 w
Switching output	Potential-free and phase- independent
Number of switching segments	84
Stand-by consumption	~0.5 W
Capacity loss max.	1.3 W
Test approval	VDE

	SUL 191 w
Housing and insulation material	High-temperature resistant, self- extinguishing thermoplastic
Type of protection	IP 20
Protection class	II according to EN 60 730-1
Ambient temperature	-20°C 55°C

# Connection example





# **SUL 191 w**

Item no.: 1910011



# Scale drawings





# Accessories

Wall mounting kit 52,5 mm Item no.: 9070050



Front panel kit Item no.: 9070001

